

**Description:**

BS-1510G label shrink tunnel adopt hot air circulating shrinkage, mainly for shrinking such containers as bottles, jars and cups etc. Variety of shrinking films, including PVC, POF etc are applicable.

Features:

1. Adopts imported parts and S/S heaters;
2. The shrink temperature is adjustable, and maximum is 250°C;
3. The conveying speed is controlled by a stepless electronic speed controller;
4. Only heat the cap of bottle, ensures products quality inside the bottle;
5. The shell of machine is made of stainless steel or painted steel;
6. Adopt two blowing motors in low power, turbo air blowing ensure the label's position and without corrugation after shrinked;
7. Can meet all kinds of bottles just need to set and adjust the machine simply;
8. Can heat only part of the tunnel for some special requirement of the products so that can save the energy;
9. This item can be connected with production line.

Application:

BS-1510G label shrink tunnel an shrink label on the body as well as the cap of bottles. Transport the bottles out from the tunnel after inserting the labels, it can be used for foodstuff, beverage, pharmacy, cosmetics and pesticide industries.

Parameters:

	BS-1510G
Voltage(V/Hz)	AC 220/50 110/60
Power (kw)	4.5
Packing Speed (pcs/hour)	8000-12000
Max. Packing Size(ϕ ×H) (mm)	ϕ 120×400
Tunnel Size (L×W×H)(mm)	1000×150×100
Film Used	PVC, POF
External Dimension (L×W×H)(mm)	1530×400×1300