



BS-4525A



BS-4535LA

**Description:**

BS-A series shrink tunnel adopts hot-wind & down-cyclone structure, intelligence temperature control and AC variable speed regulation. There are two optional conveyors, including Teflon belt type and roller type.

**Features:**

1. Both the height of tunnel and shutters on two sides are adjustable.
2. Shrink wrapping machine BS-4525A adopts single hot wind tunnel,
3. Shrink wrapping machine BS-4535LA & BS-6535LA are designed with lengthened double hot wind tunnel for higher and better shrinking effect.

**Application:**

BS-A series shrink tunnel are applied to heat shrinkable film such as PVC, POF, PP etc,

**Parameters:**

	<b>BS-4525A</b>	<b>BS-4535LA</b>	<b>BS-6535LA</b>
<b>Voltage(V/Hz)</b>	220/50(single phase) 380/50(3 phase) 220/60(3 phase)	380/50(3 phase) 220/60(3 phase)	
<b>Power(kw)</b>	6.5	9.6	12.8
<b>Loading(kg)</b>	10	30	
<b>Speed(m/min)</b>	0~10		
<b>Tunnel Size(L×W×H)(mm)</b>	900×450×(50~250)	1200×450×(50~350)	1200×650×(50~350)
<b>External Dimensions (L×W×H)(mm)</b>	1200×650×1240	1200×650×1340	1200×850×1340
<b>Net Weight(kg)</b>	90	120	150