



BSF-5540



BSF-5540A



BSF-7060

Description:

L-seal hood shrink packaging machine combines sealing with shrinking into one step. It is suitable for all kinds of shrink films such as PVC, POF, PP etc. And the transparent cover makes the process of sealing & cutting and shrinking be visible. It is equipped with height adjustable stainless steel conveying mesh, among the three models, the shrink wrapping machine BSF-5540A is used to convey the packed products out automatically so as to double packing capacity.

Features:

1. Perfect sealing without cracking and coking for adopting nano-fiber cutter holder and anti-sticking thermo-stable nichrome cutter.
2. Special-designed roller with pin to produce small holes on the film to release air.
3. Adjustable sliding film support according to the size of packing object.
4. Low power consumption, only 2.5kw/hour on average.
5. With thermo-stable and durable plastic cutter clip.
6. Inside the chamber, adjustable package support to meet different products' sizes.

7. Can be moved or fixed freely for truckles with brake fixed on the bottom of supporting base.

8.Can be operated continuously for a long time without overheating ambient environment.

Application:

1. This shrink wrapping machine is widely applied for outer shrink packing of various products, such as foodstuff, beverage, pharmacy, video disc, hardware, cosmetics, book, toy and electronic products etc.

2.To shrink wrapping the combined products in supermarket for sales promotion, such as foodstuff, beverage, cosmetics, presswork and toy etc.

3. To use in place where there is restriction on space, such as supermarket, monopolization shop, office and some laboratory etc

Parameters:

	BSF-4030	BSF-5540	BSF-5540A	BSF-7060
Voltage (V/Hz)	Single Phase 220/50			
Power (kw)	3.8	4	4.2	4
Packing Speed (pcs/h)	500-800		800-1000	500-800
Max. Packing Size (LxWxH) (mm)	350x250x150	450x300x200		600x500x300
Max. Sealing & Cutting Size (LxH) (mm)	400x300	550x400	550x400	700x600
External Dimensions (LxWxH)(mm)	1215x590x1020	1380x690x1065	1985x690x1065	1670x870x1080
Net Weight (kg)	100	125	140	140