



DZ-800/2L



DZ-900/2L



DZ-1000/2L



DZ-1100/2L

Description:

DZ/2L series single chamber vacuum packaging machine can finish the whole programs of vacuum extraction, gas flushing (optional), sealing, printing, cooling and exhaust automatically. The products after packing can be prevented from oxidation, going mould, insects or getting damp, thus can be kept fresh for longer time.

Features:

Two mutually perpendicular sealing bars. One is short, the other is long. You can choose as required through switch inside machine body.

Note: Add letter "Q" to the model name if you need function of gas flushing when you place order.

Parameters:

	DZ-800/2L	DZ-900/2L	DZ-1000/2L	DZ-1100/2L
Voltage (V/Hz)	AC 220/50 110/60			
Motor Power (W)	750×2			
Sealing Power (instant) (W)	1000		1500	
Ultimate Vacuum Pressure (KPa)	1.0			
No. of Sealing Bars	1~2			
Chamber Dimension (L×W×H) (mm)	606×806×190	606×906×190	606×1006×190	606×1106×190
Length & Width of Sealing bar	559 660	559 762	559 864	559 965
Sealing width (mm)	10			
Volume Pump Rate (m ³ /h)	20×2			
Material of Vacuum Chamber	Stainless steel			
External Dimensions (L×W×H) (mm)	886×704×902	986×704×902	1086×704×902	1186×704×902
Net Weight (kg)	235	245	255	260