



DZQ-210HL

Description:

DZQ-210HL series automatic tray vacuum gas flushing packaging machine is controlled by a microcomputer, can automate the process of tray feeding, vacuum extraction, inert gas flushing, tray sealing and tray output. The packed products can be prevented from oxidation, going mould or getting damp, thus can be kept fresh for a long time.

Features:

1. Sealing temperature, conveying speed, vacuum extracting time and inert gas flushing time are adjustable.
2. Adopt security warning systems (eg., overload protection).
3. Order-made is available

Application:

DZQ-210HL series automatic tray vacuum gas flushing packaging machine is suitable for all kinds of plastic trays, used to pack various products (fresh food in supermarket, fast food and student's snack), of which the height is the same or lower than their trays.

Parameters:

	DZQ-210HL	DZQ-250HL
Voltage (V/Hz)	AC 220/60 (single phase)	380/50 (3 Phase)
Total Power (KW)	3.75	4.55
Sealing Power (KW)	2	2.4
Min. Absolute Pressure of Chamber (KPa)	1	
Chamber Dimension (L×W×H) (mm)	360×216×80	440×290×120
Standard Dimension of Tray (mm)	210 ×160×45	250 ×180×40
Vacuum Pump Rate (m ³ /h)	20	
Conveying Speed (m/min)	5	
Capacity (Trays/Hour)	≤ 600	
Cooling Type	Water-cooling	
External Dimension (L×W×H) (mm)	3100×1000×1500	3100×1100×1700
Net Weight (kg)	600	800