



QF-600L

**Description:**

QF-600L pneumatic sealer can be operated by hand or by pedal. For the thicker bag, you can choose pneumatic sealer QF -600L /S with function of double heating.

**Features:**

1. Easy to operate
2. Adopts compressed air as power, characterized by adjustable sealing pressure and stable quality.

**Application:**

QF-600L pneumatic sealer is widely used in chemical industry, foodstuff, feedstuff industries to seal various plastic film bags and compound bag whose sealing length is less than 600mm and weight is less than 50kg, but according to special order, the sealing length can be increased to 700mm, 800mm, 1000mm. The machine can also run together with conveyor or production line.

**Parameters:**

	QF-600L	QF-600L/S
Voltage (V/Hz)	AC 220/50 110/60	
Sealing Power (W)	250	500
Air compressor	Equipped by user	
Sealing Length (mm)	600/700/800/1000	
Sealing width (mm)	8-10	
Distance from Sealing Center to Floor (mm)	1120	
Film thickness (mm)	≤0.10	≤0.18
Height of Package (mm)	450-750	
Max. Sealing Loading (kg)	50	
Adjustable Angle of Pressing Head (°)	20	
External Dimensions (L × W × H) (mm)	720×560×1340	
Net Weight (kg)	80	84